

YK3407A

P-Channel Enhancement Mode Field Effect Transistor



康比電子
HORNBY ELECTRONIC

General Description



The YK3407A uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge and operation with gate voltages as low as 2.5V. This device is suitable for use as a load switch or in PWM applications.

Application

- PWM application
- Load switch
- Power management

Features

- $V_{DS} = -30V, I_D = -4.3A$
 $R_{DS(ON)} < 50m\Omega @ V_{GS} = -10V$
 $R_{DS(ON)} < 80m\Omega @ V_{GS} = -4.5V$
- High power and current handing capability
- Lead free product is acquired
- Surface mount package



Package Marking and Ordering Information

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity
A7SHB	YK3407A	SOT-23	Ø180mm	8mm	3000 units

Absolute Maximum Ratings ($T_A = 25^{\circ}C$ unless otherwise noted)

Parameter	Symbol	Maximum	Units
Drain-Source Voltage	V_{DSS}	-30	V
Gate-Source Voltage	V_{GSS}	±20	V
Drain Current-Continuous $V_{GS} = -4.5V, @T_A = 25^{\circ}C$	I_D	-4.3	A
Drain Current –Pulsed ^{Note1}	I_{DM}	-20	A
Maximum Power Dissipation $@T_A = 25^{\circ}C$	P_D	1.5	W
Operating Junction and Storage Temperature Range	T_J	-55 ~ +150	°C

Thermal Characteristics

Thermal Resistance, Junction-to-Ambient ^{Note2}	$R_{\theta JA}$	84	°C/W
--	-----------------	----	------

Electrical Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} = 0V, I _D = -250μA	-30	-	-	V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = -30V, V _{GS} = 0V	-	-	-1	μA
Gate-Body Leakage Current	I _{GSS}	V _{GS} = ±20V, V _{DS} = 0V	-	-	±100	nA
On Characteristics ^(Note 3)						
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _{DS} = -250μA	-1.1	-1.5	-2.1	V
Drain-Source On-State Resistance	R _{DS(ON)}	V _{GS} = -10V, I _{DS} = -4.1A	-	35	50	mΩ
		V _{GS} = -4.5V, I _{DS} = -3A	-	50	80	
Forward Transconductance	g _{FS}	V _{DS} =-5V, I _D =-4.1A	5.5	-	-	S
Dynamic Characteristics ^(Note4)						
Input Capacitance	C _{iss}	V _{DS} = -15V , V _{GS} = 0V, f =1.0MHz	-	700	-	pF
Output Capacitance	C _{oss}		-	120	-	
Reverse Transfer Capacitance	C _{rss}		-	75	-	
Switching Characteristics ^(Note 4)						
Turn-on Delay Time	T _{d(on)}	V _{DS} =-15V , RL=3.6Ω V _{GS} =-10V , R _{Gen} = 3Ω	-	8.5		ns
Turn-on Rise Time	T _r		-	4.8		
Turn-Off Delay Time	T _{d(OFF)}		-	28		
Turn-Off Fall Time	T _f		-	12.5		
Total Gate Charge	Q _g	VDS=-15V,ID=-4A,VGS=-10V	-	13	-	nC
Gate-Source Charge	Q _{gs}		-	3	-	
Gate-Drain Charge	Q _{gd}		-	2.9	-	
Drain-Source Diode Characteristics						
Diode Forward Voltage ^(Note 3)	V _{SD}	I _S =4.3A, V _{GS} =0V T _j = 25°C	-	-	-1.2	V

Notes:

1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board, $t \leq 10$ sec.
3. Pulse Test: Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 2\%$.
4. Guaranteed by design, not subject to production

Typical Electrical and Thermal Characteristics




Figure 1:Switching Test Circuit




Figure 2:Switching Waveforms




Figure 3 Power Dissipation




Figure 4 Drain Current




Figure 5 Output Characteristics










Figure 6 Drain-Source On-Resistance






Figure 13 Safe Operation Area




Figure 14 Normalized Maximum Transient Thermal Impedance

YK3407A

P-Channel Enhancement Mode Field Effect Transistor



康 比 電 子
HORNBY ELECTRONIC

SOT-23 Package Information

